



LED BAY LIGHTS



SPECIFICATION:

Input : 65V – 265V AC, 50Hz – 60 Hz

Driver Efficiency : > 0.85

PF : > 0.9

THD : < 15%

APPLICATIONS

- Warehouse, cold stores, factories, workshops, supermarkets
- Stadiums, public places
- Gardens, parks

FEATURES:

- Can be used for retrofits as well as new projects
- No ballasts or chokes required.
- Excellent substitute for HPSV / Mercury Vapor lamps
- Elegant and Sleek
- All Lights manufactured with SMD design with latest technology
- Unique Heat sink design with high surface area for quick heat dissipation
- Total isolated constant current drivers
- Aluminium body with Aluminium coated PC reflector
- Consumes 60% to 80% less energy than conventional HPSV / Mercury Vapor lamps
- No UV or RF interference
- No toxic substance like Mercury

TECHNICAL DATA:

Size (mm) Dia X height	Power (Watts)	Luminous Flux	Color Temp
300 X 280	36W	2150 lm	5000 - 6000K
300 X 280	36W	2050 lm	2700 - 3300 K
400 X 380	65W	4300 lm	5000 - 6000K
400 X 380	65W	4100 lm	2700 - 3300 K
400 X 410	102W	7100 lm	5000 - 6000K
400 X 410	102W	6850 lm	2700 - 3300 K
300 X 320	36W	2150 lm	5000 - 6000K
300 X 320	36W	2050 lm	2700 - 3300 K
400 X 410	65W	4300 lm	5000 - 6000K
400 X 410	65W	4100 lm	2700 - 3300 K
400 X 470	102W	7100 lm	5000 - 6000K
400 X 470	102W	6850 lm	2700 - 3300 K
Beam Angle	80 Deg		
CRI	85Ra		
Colors available	Warm White & Pure White		
Material	Aluminum + Polycarbonate		
Expected Life	50000 hours		
Warranty	2 Years		

NOTES

- 3) Available in pendant type & wall mounted type
- 4) Other wattage and sizes available on request
- 5) The design and specification is subject to change without prior notice.
- 6) Fitting should be carried out by qualified electricians as per the instruction manual.

Warning: Improper installation of LED Bay lights may result in failure of the product. Please follow the instructions carefully.